

ABO – CENTER

V/ Henriksens Elektronik

Rep.tips AV9000

Service tips!

Minder meget om MX6000 & MX7000 – Kan bruge de samme rep. Tips – Videon er en VX7000

Service tips!

Service mode AV9000:

TRYK – TV – KORTSLUT STIK P7000

Typisk:

4301 (Typenr.) – 00000001 (Serienr.) – Sidste error (Sidste fejlkode)

Service tips!

Se S/W version:

AV9000: TV – MENU – 0 – 0 – PLAY

SAT: SAT – MENU – 5 – 0 – 0 – PLAY

VIDEO: VTAPE – MENU – 5 – 0 – 0 – PLAY – 1

CONTROL BOX: TV – MENU – 2 – 0 – 0 – PLAY

ABO - CENTER v/Henrikse

ABO – CENTER

V/ Henriksens Elektronik

Tekniske data AVANT9000

TYPE:

43XX, 1992 - 1996

Specifications:	
Dimensions WxHxD	70,5x108x60 cm
Weight AV9000 monitor	46,5 kg
Control Center with Video	45 kg
Tape	
Cabinet finish	Black
Daily operating recommended	Beo4
Sound processing	Dolby Surround Sound Pro-logic decoder
Sound modes (sound 1-5)	Mono (Center speaker) Stereo Dolby-3 stereo Stereo-4 Dolby Surround Sound
Stand turning function	+/- 33 degrees, remote operated
Power consumption,AV	75-200 watts, std.by. 7 watts
Monitor	
AV Control Center	Max 120 watts, std.by. 15 watts
AV 9000 Monitor	
Picture tube/visual picture	Anti-reflex coated 70 cm - 28" / 66 cm - 26" Black Line S, Black Matrix
Contrast screen	Grey glass, anti-reflex coated
Vision Clear	Auto picture adjustment Auto cut-off Wideband CTI Dynamic Luminance Peaking
Teletext	Improved teletext Fastext, 6 languages,memory
TV tunes/monitor/video:	
Tuner range	VHS,S,Hyper,UHF 89 Nicam+A2
Video Tape functions:	
Video playing time, E-240	SP 4 hours,LP 8 hours
Audio playing time, E-240	LP 8 hours
Fast forward/rewind	Less than 5 minutes
Slow motion	1/7 x normal speed

ABO – CENTER

V/ Henriksens Elektronik

Still picture	Noiseless
Cue	2 x and 7 x normal speed
Recording system	HQ
Sound system	Hi-Fi stereo,video/audio
Stereo decoders	Nicam+A2
Playback NTSC	AV
Timer record programming	8,1 year, TV,SAT,FM,AM
VPS system	Built-in
Center speaker:	
Sound Pressure Level	97 dB(mono)
Frequency range	+4 dB - 8 dB 60 - 20,000 Hz
Cabinet principlke/net volume	Bass Reflex/2,4 litres
Woofers	11,5 cm - 4,5"
Tweeter	1,8 cm - 3/4"
Crossover frequency	3200 Hz
Connections:	
Video: Tape 2/decoder	AV 2,21-pin AV Link
Camcorder/Auxiliary	3 x phono sockets
Camera pause	Mini Jack
S-VHS	Y-C playback 4-pin socket
Audio	1 x Master Link
Link compatibility:	
Master Link	

ABO – CENTER

V/ Henriksens Elektronik

Tekniske data AVANT9000 BE04

TYPE:

79XX, 1995 - 1996

Specifications:	
Dimensions WxHxD	70,5x108x60 cm
Weight AV9000 monitor	46,5 kg
Control Center with Video	45 kg
Tape	
Cabinet finish	Black
Daily operating recommended	Beo4
Sound processing	Dolby Surround Sound Pro-logic decoder
Sound modes (sound 1-5)	Mono (Center speaker) Stereo Dolby-3 stereo Stereo-4 Dolby Surround Sound
Stand turning function	+/- 33 degrees, remote operated
Power consumption,AV	75-200 watts, std.by. 7 watts
Monitor	
AV Control Center	Max 120 watts, std.by. 15 watts
AV 9000 Monitor	
Picture tube/visual picture	Anti-reflex coated 70 cm - 28" / 66 cm - 26" Black Line S, Black Matrix
Contrast screen	Grey glass, anti-reflex coated
Vision Clear	Auto picture adjustment Auto cut-off Wideband CTI Dynamic Luminance Peaking
Teletext	Improved teletext
	Fastext, 6 languages,memory
TV tunes/monitor/video:	
Tuner range	VHS,S,Hyper,UHF 89 Nicam+A2
Video Tape functions:	
Video playing time, E-240	SP 4 hours,LP 8 hours
Audio playing time, E-240	LP 8 hours
Fast forward/rewind	Less than 5 minutes
Slow motion	1/7 x normal speed

ABO – CENTER

V/ Henriksens Elektronik

Still picture	Noiseless
Cue	2 x and 7 x normal speed
Recording system	HQ
Sound system	Hi-Fi stereo,video/audio
Stereo decoders	Nicam+A2
Playback NTSC	AV
Timer record programming	8,1 year, TV,SAT,FM,AM
VPS system	Built-in
Center speaker:	
Sound Pressure Level	97 dB(mono)
Frequency range	+4 dB - 8 dB 60 - 20,000 Hz
Cabinet principlke/net volume	Bass Reflex/2,4 litres
Woofers	11,5 cm - 4,5"
Tweeter	1,8 cm - 3/4"
Crossover frequency	3200 Hz
Connections:	
Video: Tape 2/decoder	AV 2,21-pin AV Link
Camcorder/Auxiliary	3 x phono sockets
Camera pause	Mini Jack
S-VHS	Y-C playback 4-pin socket
Audio	1 x Master Link
Link compatibility:	
Master Link	

ABO – CENTER

V/ Henriksens Elektronik

Tekniske data AVANT9000IT

TYPE:

797X, 1996 - 2000

Specifications:	
Dimensions WxHxD	70,5x108x60 cm
Weight AV9000 monitor	46,5 kg
Control Center with Video	45 kg
Tape	
Cabinet finish	Black
Daily operating recommended	Beo4
Sound processing	Dolby Surround Sound Pro-logic decoder
Sound modes (sound 1-5)	Mono (Center speaker) Stereo Dolby-3 stereo Stereo-4 Dolby Surround Sound
Stand turning function	+/- 33 degrees, remote operated
Power consumption,AV	75-200 watts, std.by. 7 watts
Monitor	
AV Control Center	Max 120 watts, std.by. 15 watts
AV 9000 Monitor	
Picture tube/visual picture	Anti-reflex coated 70 cm - 28" / 66 cm - 26" Black Line S, Black Matrix
Contrast screen	Grey glass, anti-reflex coated
Vision Clear	Auto picture adjustment Auto cut-off Wideband CTI Dynamic Luminance Peaking
Teletext	Improved teletext
	Fastext, 6 languages,memory
TV tunes/monitor/video:	
Tuner range	VHS,S,Hyper,UHF 89 Nicam+A2
Video Tape functions:	
Video playing time, E-240	SP 4 hours,LP 8 hours
Audio playing time, E-240	LP 8 hours
Fast forward/rewind	Less than 5 minutes
Slow motion	1/7 x normal speed

ABO – CENTER

V/ Henriksens Elektronik

Still picture	Noiseless
Cue	2 x and 7 x normal speed
Recording system	HQ
Sound system	Hi-Fi stereo,video/audio
Stereo decoders	Nicam+A2
Playback NTSC	AV
Timer record programming	8,1 year, TV,SAT,FM,AM
VPS system	Built-in
Center speaker:	
Sound Pressure Level	97 dB(mono)
Frequency range	+4 dB - 8 dB 60 - 20,000 Hz
Cabinet principlke/net volume	Bass Reflex/2,4 litres
Woofers	11,5 cm - 4,5"
Tweeter	1,8 cm - 3/4"
Connections:	
Video: Tape 2/decoder	AV 2,21-pin AV Link
Camcorder/Auxiliary	3 x phono sockets
Camera pause	Mini Jack
S-VHS	Y-C playback 4-pin socket
Audio	1 x Master Link
Link compatibility:	
Master Link	